

CONTI® SYNCHROTWIN CXP

Heavy-duty double-sided timing belts for high speeds

Properties:

- ▶ conditionally resistant to oil
- ▶ temperature range, depending on application, from -20°C to +100°C
- ▶ electrically conductive to ISO 9563
- ▶ suitable for tropical climates
- ▶ resistant to aging and ozone
- ▶ maintenance-free
- ▶ suitable by counterbending
- ▶ increased power ratings



DHTD

Profile	Length range L_p (mm)
DHTD D5M CXP	565 - 2000
DHTD D8M CXP	600 - 2600
DHTD D14M CXP	966 - 2450

DSTD

Profile	Length range L_p (mm)
DSTD DS8M CXP	600 - 2392

Heavy-duty variant
CONTI® SYNCHROTWIN CXA
for low speeds and
high torque on request.

Power Transmission Group

Market segment
Industry

Contact
ContiTech Antriebssysteme GmbH
D-30169 Hannover

Phone +49 511 938 - 71
industrie.as@ptg.contitech.de

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2012 ContiTech AG. All rights reserved. For complete information go to: www.contitech.de/disc_en